

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A shield connection structure comprising:

a conductive shield member ~~including~~ comprising:

a plate member having a hole in which a shielded wire is inserted;₁

a connection portion for connecting to a shielding portion of the shielded wire;₁ and

a reinforcing rib formed on a peripheral edge portion of said shield member;₁ wherein:

said shield member is fixed to a casing for grounding; and

~~wherein~~ said reinforcing rib and said shield member are formed of a one-piece

construction; and

said shielded wire includes a braided wire and said connection portion is dimensioned so that said braided wire can be folded over the exterior of the connection portion.

2. (Original) A shield connection structure according to claim 1, wherein said connection portion has a tubular shape, and is formed on and projects perpendicularly from an end portion of said hole for passing said shielded wire therethrough.

3. (Original) A shield connection structure according to claim 1, wherein said reinforcing rib is formed in a continuous manner on the peripheral edge portion of said shield member over an entire periphery thereof.

4. (Cancelled)

5. (Original) A shield connection structure according to claim 1, wherein said shielding member and said reinforcing rib are constituted by one and the same component.

6. (Currently Amended) A shield member fixed to a casing for grounding comprising:

a plate member having a hole;

C' Cont. a connection portion having a tubular shape provided around the hole for supporting and connecting to a shielding portion of a shielded wire; and

a reinforcing rib integrally formed on a peripheral edge portion of said shield member, wherein:

said reinforcing rib and said shield member are formed of a one-piece construction; and

said shielded wire includes a braided wire and said connection portion is dimensioned so that said braided wire can be folded over the exterior of the connection portion.

7. (New) A shield connection structure according to claim 1, further comprising a ring which is fitted on the exterior of said braided wire.

8. (New) A shield connection structure according to claim 6, further comprising a ring which is fitted on the exterior of said braided wire.

9. ^{x 1}(New) A shield connection structure comprising:

a conductive shield member comprising:

a plate member having a hole in which a shielded wire is inserted;

a connection portion provided to contact a shielding portion of the shielded wire; and

a reinforcing rib formed on a peripheral edge portion of said shield member, wherein

said shield member is fixed to a casing for grounding; and

said reinforcing rib, said connection portion and said shield member are formed of a one-

piece construction.

Cmt. ^{x 2}
10. (New) A shield connection structure according to claim 9, wherein said connection portion has a tubular shape, and is formed on and projects perpendicularly from an end portion of said hole for passing said shielded wire therethrough.

^{x 3}
11. (New) A shield connection structure according to claim 9, wherein said reinforcing rib is formed in a continuous manner on the peripheral edge portion of said shield member over an entire periphery thereof.

^{x 5}
12. (New) A shield connection structure according to claim 9, wherein said shielding member and said reinforcing rib are constituted by one and the same component.

^{x 6}
13. (New) A shield member fixed to a casing for grounding comprising:

a plate member having a hole;

a connection portion having a tubular shape provided around the hole to support and contact a shielding portion of a shielded wire; and

a reinforcing rib provided on a peripheral edge portion of said shield member, wherein said reinforcing rib, said connection portion and said shield member are formed of a one-piece construction.

C. cnt.
14. (New) A shield connection structure comprising:

a conductive shield member comprising:

a plate member having a hole in which a shielded wire is inserted;

a connection portion for connecting to a shielding portion of the shielded wire; and

a reinforcing rib formed on a peripheral edge portion of said shield member; wherein:

said shield member is fixed to a casing for grounding;

said reinforcing rib and said shield member are formed of a one-piece construction; and

said reinforcing rib and said connection portion extend in opposite directions from said plate member, and are located only on opposite sides of said plate member.

Case admitted
15. (New) A shield connection structure according to claim 14, wherein said connection

portion has a tubular shape, and is formed on and projects perpendicularly from an end portion of said hole for passing said shielded wire therethrough.

16. ^{x 3}(New) A shield connection structure according to claim 14, wherein said reinforcing rib is formed in a continuous manner on the peripheral edge portion of said shield member over an entire periphery thereof.

17. ^{x 5}(New) A shield connection structure according to claim 14, wherein said shielding member and said reinforcing rib are constituted by one and the same component.

C.
cont.

18. ^{same as 14}(New) A shield member fixed to a casing for grounding comprising:
a plate member having a hole;
a connection portion having a tubular shape provided around the hole for supporting and connecting to a shielding portion of a shielded wire; and
a reinforcing rib provided on a peripheral edge portion of said shield member, wherein:
said reinforcing rib and said shield member are formed of a one-piece construction; and
said reinforcing rib and said connection portion extend in opposite directions from said plate member, and are located only on opposite sides of said plate member.
